UDF-21 FOR DECKS. 21POLYPLUSTM FOR MARINE PILINGS.

COMPARE ULTIMATE COATINGS TO YOUR FAVORITE COATING AND YOU'LL SEE THE VALUE!

Features and Benefits (check all that apply)	UF Coatings	The Next best
	oounigs	Option
A Do-It-Yourself Coating	✓	
Easy to Apply	\checkmark	
High Build, Quick Setting	~	
Unlimited color range	~	
Tools clean up with water	~	
Lasts' for years	✓	
Locks down splinters	~	
Helps inhibit rust bleed-through from nails & fasteners	~	
Zero to little maintenance required	✓	
Fire resistant	✓	
Looks great for years	✓	
Great on bare feet	✓	
A fraction of the cost of replacement	✓	
Stain resistant	✓	
Scuff resistant	✓	
No VOCs	~	
Environmentally friendly	✓	
Non-toxic to human or aquatic life	~	
Encapsulates wood treatment	\checkmark	
Prevents marine borer attack (UPF-14)	\checkmark	
Easy to patch when damaged	\checkmark	

Our Ultimate Formulations are water-based polymeric coatings that allow you to choose custom colors by simply mixing a common latex paint into the kit. Brush or roll on. Dries quickly. Minutes, not hours, between coatings. Open to foot traffic within a few hours. Dries into a tough, durable coating. Provides fantastic skid resistance to all types of surfaces.

Distributed By:



gulfsynthetics.com

With the other guys, your color options for an outdoor deck are limited.

Imagine an option with unlimited colors...

Now you're thinking.



Your color palette is unlimited when you use UDF-21.

A pastel here. A wood tone there. The color options available for an outdoor deck are cliché at this point.

That's one of the reasons you should consider the benefits of UDF-21, a new do-it-yourself coating that among many other benefits, allows you to pick any color you choose for your next deck project. Simply add a gallon of pigmented exterior latex paint to the UDF-21 kit, mix, and apply. It's that simple!

UDF-21 is a water-based polymer coating that cross-links with latex paint to form a hard, durable, protective coating that protects your wood deck from the harmful effects of the sun and rain.

UDF-21 is also safe. The built-in skid resistant aggregate helps to prevent accidents, while still feeling great on bare feet. UDF-21 locks down nail heads and splinters so quiet afternoons on the deck aren't broken by the shrill of someone who unexpectedly finds a nail or splinter.

UDF-21 is applied quickly using a paint roller. UDF-21 dries so fast that this mornings deck project can be the hit of tonight's grill-out.

So express yourself in your next deck project at a fraction of the cost of replacement.

UDF-21 is available in a 2.5 gallon kit. Add one gallon of your choice of exterior latex to make a total 3.5 gallon mix. Coverage varies based on the condition of the wood substrate and the thickness in which the coating is applied. Expect approximately 400 square feet of coverage per kit (2 coats required). Apply with sponge roller. Clean tools with water. Once the kit is mixed, the activated mix has a 14 day shelf life in a sealed container. Never modify the kit beyond adding the paint requirement.

Consult your deck or painting professional for answers to other questions.

Distributed By:



Someone Trying to Tell You Something About Your Wood Deck?



You've got the point. The annual ritual and expense of staining and sealing your deck yields no long-term benefit, and each year splinters and nail heads become a larger threat to bare feet.

UDF-21 Deck Formulation is a unique & beautiful coating that is easily applied to wood and provides protection against splinters, nails, and other things that can ruin a great afternoon around the pool.

UDF-21's durable, high-build coating creates a comfortable walking surface while locking down years of weathering.



Best of all, you decide on the color! Simply add one gallon of exterior latex paint in the color of your choice to the kit and apply. It really is that simple! UDF-21 is also cool on bare feet. Its special formulation allows the wood below to draw heat down so the surface stays cool.

UDF-21 is water-based – so it's safe. It's also quick. This morning's deck project is the hit of this evening's grillout.

Yesterday they jumped for one reason. Today they jumped for another.

Learn more about UDF-21 by visiting the Dealer below.



Does the Last Storm Have You Singing the Deckless Pier Blues?





UDF-21 is applied to a wooden dock using a roller. One kit covers approximately 400 square feet (2 coats required).

All of a sudden, that expensive composite decked pier is ravaged by a storm and your investment has vanished.

You won't make that same mistake twice, because you've just discovered UDF-21, an inexpensive coating that makes everyday treated lumber perform just like an expensive composite deck board.

UDF-21 is a durable DIY polymer coating designed specifically for wood. This water-based product is easy to apply and cures in minutes. This morning's dock project quickly becomes the center of this evening's festivities.

UDF-21 locks down splinters and covers old fasteners. Its comfortable skid resistant surface stays cool as the wood below pulls heat away.

Best of all, UDF-21 is available in any color. Simply mix one gallon of exterior latex in the color of your choice and it's done. Its look is pure perfection.

So don't sink a fortune in your dock when for a fraction of the cost of other deck products you can own the smartest choice.

For more information, contact your local UDF-21 dealer today!

Distributed By:

BASIC MIXING & USE INSTRUCTIONS FOR 21POLYPLUS_{tm}.

Points To Keep in Mind:

- Wood surface MUST be clean and dry.
- 21POLYPLUS will dry faster on warmer, sunny days.
- If you are using more than one kit for a project, you must empty the entire paint requirement into the pail or the color may be inconsistent between kits.
- Parts must be cured prior to installation (See below).
- Keep a lid on any surplus coatings and store in a cool, dark area.
- Clean tools with water and store.

1. Empty resin into container.



2. Empty $\frac{1}{2}$ gallon or two quarts of exterior latex paint into container. Use only exterior latex or acrylic paint.



3. Using drill blender, blend the wet ingredients.



4. Gradually mix in the dry ingredients. Mix briskly and thoroughly for five minutes. Mix should be creamy and should have a viscosity similar to cake batter.



5. Using a 3/8th nap roller, liberally, but evenly, spread a base coat of 21POLYPLUS over the pile. Allow to dry.



6. Once base coat is dry to the touch, apply the topcoat. Be consistent with technique!



IMPORTANT Coated parts require a 48 hr. cure <u>process</u>.

CURING PROCESS:

- After coating, allow parts to sit and dry for 12 hours.
- Using a water hose, wet dried parts thoroughly to activate organic additives.
- Allow parts to sit and dry for 12 hours.

BASIC MIXING & USE INSTRUCTIONS FOR UDF-21.

1. Empty resin into container.



2. Empty paint requirement into container. UDF-21 requires 1 gallon. Use only exterior latex or acrylic paint.



3. Blend the wet ingredients until thoroughly mixed.



Other Points:

- Substrate MUST be clean and dry.
- Coatings will dry faster on warmer, sunny days.
- Always provide 48 hours of curing before installing UPF-14 in the water.
- If you are using more than one kit for a project, you must empty the entire paint requirement into the pail or the color may be inconsistent between kits.
- Clean tools with water and store.
- Keep a lid on any surplus coatings and store in a cool, dark area.

4. Gradually mix in the dry ingredients. Mix briskly and thoroughly for five minutes. Mix should be creamy and should have a viscosity similar to cake batter.



5. Using brush, fill in nail heads and bad checks.



6. Using a nap roller, apply the base coat. A heavier second coat is applied once the base coat is dry. The top coat is key to attaining the proper texture. Be consistent in your technique!

