

SYNERGY[®] MPL

Narrow-plank Xcora™ Strand Solid Bamboo Flooring



FINE BAMBOO FLOORING, PANELS & WORKTOPS

Teragren's best selling narrow-plank profile combined with our Xcora™ strand bamboo comes in Multiple Precise Lengths of 2,3,4 and 6 feet for an intentionally random visual when installed. Featuring a tongue and groove profile for flexible installation. Designed for use in commercial and residential interiors.



FEATURES + BENEFITS

PERFORMANCE

- Durable 9-step UV Cured Polyurethane coating with aluminum oxide wear layer for abrasion resistance
- Premium Xcora strand bamboo – 160% harder than Red Oak*
- Optimum 5.5 Moso Bamboo: Harvested at maturity for peak density, creating a harder and more stable product for lasting beauty and performance
- Approved for installation over radiant heat flooring systems

VALUE

- Lifetime structural warranty; 10-year heavy-use commercial/25-year residential finish warranties

ECOSMART

- Certified USDA BioPreferred – 94% biobased content

INDOOR AIR QUALITY


- Floorscore certified for superior indoor air quality.
- Qualifies for Collaborative for High Performance Schools 2009 Criteria EQ2.2.3 – Low Emitting Materials



SYNERGY® MPL Java

PRODUCT DETAILS

Nominal Dimensions :	24, 36, 48 & 72" x 3.78" x 0.47" 610mm, 915mm, 1220mm & 1830mm x 96mm x 12mm
Construction:	Solid Xcora™ Strand Bamboo
Milling:	4 side Micro Bevel
Profile:	Tongue and groove
Accessories:	Full line of coordinating 12mm accessories
Color Variation:	Moderate




INSTALLATION + CARE


Installation Environment:	Nail or Glue installation into environments having 35-55% RH. Can be installed over radiant heat.
Nail Installation:	On or Above grade. Use vapor retarder over wood subfloor.
Glue Installation:	On or Above grade. Use a vapor barrier over cement subfloor OR vapor retarder over wood subfloor.
Recommended Adhesive:	Premium Wood Flooring Adhesive
Nailing Guidelines:	18 -20 gauge cleat by 1 1/2"
Acclimation:	Minimum of 48 hours on-site in box
Maintenance:	TrueClean Floor Cleaner

LEED[®] CREDITS


- IEQ 4.3 Low Emitting Materials
- MR6 Rapidly Renewable Materials



Java



Chestnut



Wheat

*Xcora™ bamboo is 160% harder than Red Oak.