SafeChoice Carpet Shampoo Usage Guidelines

USE ON:

Synthetic carpets and rugs, because of variations in materials and production processes used by different manufacturers, you should always spot test to insure compatibility with your carpet.

Not recommended for wool.

LIMITATIONS:

Water cleaning of wool tends to shrink the fabric and, due to natural fiber absorption, can pull dirt back into the fibers. Always spot test carpet in an inconspicuous location for color fastness and compatibility. When using carpet products it is advisable to put small squares of aluminum foil under the furniture legs until carpet is thoroughly dry.

DILUTION PER GALLON OF WATER:

Light cleaning - 3 fluid ounces. Medium cleaning - 5 fluid ounces. Heavy cleaning - 8 fluid ounces. One gallon of diluted solution will clean approximately 300 square feet.

APPLICATION:

SafeChoice Carpet Shampoo should be applied using a hand-held pump sprayer. One similar to a garden sprayer is most effective. Prior to application vacuum carpet thoroughly. Using the applicable dilution rate specified above, spray the carpet evenly, saturating the surface. Allow the shampoo ten minutes to fully penetrate. Then extract the shampoo with very clean, very hot water. By extracting with only clean, hot water the carpet is not only cleaned more effectively but the removal of residue from prior cleanings is accomplished. While the foregoing procedure yields the best results, SafeChoice Carpet Shampoo may also if desired be added to any shampooing or carpet cleaning machine.

CLEAN-UP:

Clean tools and equipment while they are still wet with a warm soapy water solution.

HEALTH PRECAUTIONS:

As with all cleaners, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation.

PHYSICAL DATA

Physical Description:Clear, odorlesspH:9.5Solubility in Water:Complete% Volatile by Weight:N/AVOC Material less H20:0 g/lHAP's (Hazardous Air Pollutants) zero

If you are chemically sensitive, always test for personal tolerance. Test samples available here: www.greenbuildingsupply.com



LIMITED LIABILITY: Liability, whether express or implied, is limited solely to replacement of product shown to be defective when applied in accordance with instructions and shall under no circumstances include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for its intended use. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. We particularly recommend that users always test in small inconspicuous areas before application to the entire surface. American Formulating and Manufacturing 3251 Third Ave., San Diego, CA 92103 www.afmsafecoat.com.