

Installation Guidelines

WATER BASED/COVERAGE: See specifications below.

USE ON:

Wood and metal frame construction interior and exterior paneling, Drywall and gypsum-board. Bonds cove base, tub surrounds and fiberglass. Works on landscape blocks, concrete, masonry, ceramic tile and ceiling tile. Excellent for decorative brick and stone, wood decking and sub-floor Installation

LIMITATIONS:

Safecoat adhesives are made without formaldehyde preservatives. Do not contaminate. Do not use when temperature is below 40°F. Best curing temperatures are above 55°F and rising.

SURFACE PREPARATION:

Surface must be completely dry and stable prior to application. Remove all dirt, dust, oils, grease, wax, dried out fillers, powdery residue and other foreign materials. Use alcohol to clean surfaces if necessary.

APPLICATION:

Apply beads of adhesive to clean bonding surfaces using a standard caulking gun and assembly, making sure bonded materials are tightly joined. Use mechanical fasteners as needed to fixture materials, or as specified by code. Keep tube closed and tip covered when not in use. Because Safecoat does not use toxic mildewcides, fungicides, preservatives or solvent softening agents, material can solidify if unused with one year of purchase.

COVERAGE:

10.1 oz. tube covers approximately 25 linear feet at .25" thickness.

CLEAN-UP:

Clean tools and equipment while they are still wet with a warm soapy water solution. Dried material may require alcohol for cleaning.

DRYING/CURING TIME:

Allow 24 hours for a full cure.

HEALTH PRECAUTIONS:

As with all coatings and sealers, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation.

PHYSICAL DATA

Boiling Point:	NA
Melting Point:	N/A
Volatile by Volume:	0%
% Volatile by Weight:	0%
VOC Material:	Less than 35 g/l @240°

HAP's (Hazardous Air Pollutants) zero

**If you are chemically sensitive,
always test for personal tolerance.**

Test tubes available here:

www.thegreendesigncenter.com

