

Technical Data Sheet	Standard	Unit	Value
Dimension (LxWxT)	EN 427	mm	600 ± 0.5% 300 ± 0.5%
Mass per unit	-	Kg/m ²	0,95
Packaging (box / pallet)	-	m ²	5,94 / 213,84
SQUARENESS	EN 427	mm	600: < 1.0mm 300: < 0.5mm
THICKNESS	ISO 7322	mm	3.0 ± 0.3%
APPARENT DENSITY	EN 672	Kg/m ³	≥ 200
DIMENSION STABILIT	EN 434	%	3.0 ± 0.3%
CURLING	EN 434	mm	≤ 6
MOISTURE CONTENT	EN 12105	%	≤ 7
FORMALDEHYDE	EN 12149, method C	mg/Kg	≤ 95
VINYL CHLORIDE MONOMER (VCM)	EN 12149, TEST B	mg/Kg	≤ 0,2
THERMAL RESISTANCE	EN 12667	m ² K/w	0.0572 (Varnished) 0.0583 (Waxed)
REACTION TO FIRE	EN 15102:2007	Class	E
SOUND ABSORPTION	ISO 354	αw	0,1
RELEASE OF HEAVY METALS AND SPECIFIC ELEMENTS	EN 12149		fulfilled