

Company Overview

Products

Contact Us

MATERIAL SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product Name: CALIWEL WITH BNA / ANTIMICROBIAL PAINT / COATING

Date: 10/2018

CALCIUM HYDROXIDE (HYDRATED LIME) BASED

Prodcut Code: 73696-2

Emergency: National Response Center (800) 424-8802

ALISTAGEN CORPORATION

Ten Park Avenue

New York, New York 10016

EPA REG. NO. 73696-2

SECTION 2. HAZARDS

GHS Ratings

Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: $\geq 2.3 < 4.0$ or persistent inflamoatory
Eye corrosive	2B	Mild eye irritant: Subcategory 2B, Reversible in 7 days
Carcinogen	2	Limited evidence of human or animal carcinogenicity
Organ toxin single exposure	3	Transient target organ effects - Narcotic effects - Respiratory tract irritation

GHS Hazards

H315+H320	Causes skin and eye irritation
H319	Causes eye irritation

GHS Precautions

P260	Do not breathe dust/fume/gas/mist/vapors/spray
P264	Wash ... thoroughly after handling
P281	Use personal protective equipment as required
P363	Wash contaminated clothing before reuse
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P405	Store locked up
P501	Dispose of contents/container in accordance with state and local regulations.

Signal Word: Danger



SECTION 3. COMPOSTION

Chemical Name	CAS number	Weight Concentration %
TITANIUM DIOXIDE	13463-67-7	10.00% - 20.00%

SECTION 4. FIRST AID MEASURES

Remove the effected individual into fresh air and keep person calm. Seek medical attention.  
If in eyes: Immediately flush effected eyes for at least 15 minutes under running water with eyelids held open.

Wash effected area thoroughly with soap and water. Seek medical attention

If swallowed: Immediately rinse mouth and then drink plenty of water, do not induce vomiting, seek medical attention.

Never induce vomiting or give anything by mouth if victim is unconscious or have convulsions. Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5. FIRE FIGHTING MEASURES

Fire Extinguishing Media: Non-Flammable

Fire & Explosion Hazard Data (ASTM E84)  
Flash Point (F): NA  
Flame Spread Index (FSI): 0

Smoke Developed Index (SDI): 0  
Ignition Time (Min:Sec): None  
Maximum Temp. at Exposed TC (F°): 560

Time to Maximum Temp. (Min:Sec): 9:42  
Flaming on Floor: None  
Afterflame Top (Min:Sec): None  
Afterflame Florr (Min:Sec): None  
LEL: 1.0%  
UEL: 5.0%  
Flammability Classification: Non-Flammable  
DOT: No information Special Fire Fighting Procedures: NA  
Unusual Fire and Explosion Hazards: NA

SECTION 6. ACCIDENTIAL RELEASE MEASURES

Spills should be contained, solidified, and placed in suitable containers for disposal. In the case of release to the environment, report spills to the National Response Center 1-800-424-8802.

Dispose of absorbed material in accordance with all local, state and federal regulations. For Hazardous Waste Regulation: Call the RCRA Hotline at 1-800-424-9346.

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder). Pump off product.

SECTION 7. HANDLING AND STORAGE

General advice: No special measures necessary provided product is used correctly.

General advice: Keep container tightly closed and in a cool place.

SECTION 8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits
TITANIUM DIOXIDE 13463-67-7	DRY ONLY: PEL - 15 Mg/m3	DRY ONLY: PEL - 15 Mg/m3

Respiratory protection: Wear respiratory protection if ventilation is inadequate. Respiratory protection in case of vapor/aerosol release.

Hand Protection: Chemical resistant protective gloves.

Eye Protection: Tightly fitting safety goggles (chemical goggles) and face shield

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Range 100 to 270 °C%	Weight Solids 3.25
% Weight Water 26.11%	Weight Volatile (VOC) 0.00
% Volume Volatile 0.00	Specific Gravity (SG) 1.424
% Weight Solids 3.25	Evaporation Rate (Butyl Acetate = 1): Slower than Ether
% Volume Volatile (VOC) 0.00	pH @ 77F: 12.4
Grams VOC/Liter Less Water 0.0	LBS VOC / Gallon Less Water 0.00
Coverage (sq. ft/gal. @1 mil) 0	

SECTION 10. REACTIVITY

Conditions to avoid:

No conditions that should be avoide

Substances to avoid:

No substances known that should be avoided.

Hazardous reactions:

No hazardous reactions when stored and handled according to instructions. The product is chemically stable.

Incompatible Materials: Strong oxidizing agents

No hazardous decomposition products if stored and handled as prescribed/indicated.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, organic products of combustion, oxides of sulfur.

Hazardous polymerization will not occur.

SECTION 11. TOXICITY

Mixture Toxicity  
Inhalation Toxicity LC50: 28mg/L

Component Toxicity

13463-67-7                    TITANIUM DIOXIDE

Oral LD50: 5,000 mg/kg (RAT) Dermal LD50: 5,000 mg/kg (RABBIT) Inhalation LC50: 7 mg/L

Routs of entry of solids and liquid eye and skin contact. Routs of entry for gasses include inhalation and eye contact. Skin contact may be a rout of entry for liquefied gasses.

Effects of Overexposure

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
None			N/A

Virtually nontoxic after single ingestion.

Repeated dose Toxicity:

Repeated oral uptake of substance did not cause substance-related effects. Repeated exhalative uptake of the substance did not cause substance-related effects. Repeated dermal uptake of the substance did not cause substance-related effects.

The product has not been tested. The statement has been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL

Component Ecoxicity.

SECTION 13. DISPOSAL

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent

unauthorized use of container

SECTION 14. TRANSPORT

Land transport:

USDOT Not classified as a dangerous good under transport regulations

Sea transport:

IMDG Not classified as a dangerous good under transport regulations

Air transport:

IATA Not classified as a dangerous good under transport regulations

Agency	Proper Shipping Name	UN Number	Packing Group	Hazard Class
DOT	PAINT	non-hazardous	non-regulated	water-based or latex

SECTION 15. REGULATORY

	Components Listed	Country	Regulation	All
EU Risk Phrases				
Safety Phrase				
- None				

SECTION 16. OTHER INFORMATION

HMIS III rating

Health: 1 Flammability: 0 Physical hazard: 0

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

Hazardous Material Information System (HMIS)

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

HMIS & NFPA Hazard Rating Legend

\* = Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. END OF DATA SHEET.

[Company Overview](#)  
[Sitemap](#)

[Products](#)

[Contact us](#)

[Terms & Conditions](#)

© Alistagen Corporation. All rights reserved.

SECURE

DATA ENCRYPTED

ns network solutions

SECURE

DATA ENCRYPTED

ns network solutions

Join the conversation

YouTube™