



ECOS INTERIOR AIR PURIFYING PAINT APPLICATION INSTRUCTIONS

| | |
|---------------------------------|--|
| Recommended For | Walls & ceilings, windows, doors, trim, furniture, cabinets and other woodwork, including use in kitchens and bathrooms |
| Coverage | 500 sq. ft. per gallon 125 sq. ft. per quart; 2 coats recommended |
| Description | Air Purifying Paint is a protective finish that dries to a hard, washable, durable film. Ideal for interior/exterior walls, furniture, and trim, including use in kitchens and bathrooms. This paint absorbs and neutralizes chemicals, pollutants and VOCs for improved indoor air quality. Available in four sheens: Matte, Eggshell, Semi-Gloss & Gloss. |
| Preparation | Good surface preparation is vital for the perfect finish. Surfaces should be clean, dry, and free from any dirt, dust, or contaminants. Repair any cracks, holes, or imperfections. Sand glossy surfaces with fine grit sandpaper first to ensure good adhesion. Before painting, clean stubborn areas with mild detergent, and remove any loose, or peeling paint, then rinse and dry thoroughly before painting. ECOS Paint is self-priming on most properly prepared surfaces, but we recommend using one of our primers if painting over a higher gloss finish, a darker color, or applying an accent color. |
| Application and Clean Up | Stir well before use. If using multiple containers of the same color, intermix them all to ensure color uniformity. Can be applied using a high quality synthetic brush, rolled using a shed-resistant 3/8" to 1/2" roller cover, or sprayed using an airless sprayer with 0.015" to 0.017" tip at 1600 to 1800 psi. Do not apply in temperatures below 50°F (10°C). For best results, always apply two coats of paint. Dries to the touch in 30 to 60 minutes. Recommended wait time between coats is 2 to 4 hours. High humidity and cool temperatures may result in longer dry and recoat times. Do not thin the paint. Clean up with warm soapy water. |