



## ECOS INTERIOR ANTI-SLIP FLOOR PAINT APPLICATION INSTRUCTIONS

<b>Recommended For</b>	Use on bare and previously painted wood and concrete floors
<b>Coverage</b>	400 sq. ft. per gallon   100 sq. ft. per quart; 3 coats recommended
<b>Description</b>	Interior Anti-Slip Floor Paint is a medium sheen hard, washable, durable, finely-textured, floor paint for interior use on bare and previously painted wood and concrete floors. Designed to help protect against hazardous conditions in locations that see a lot of foot traffic, from hallways to entryways, Anti-Slip Floor Paint can help reduce surface slickness.
<b>Preparation</b>	Surfaces should be clean, dry, sound, and free from dirt, dust, grease, and loose or flaking material. Clean stubborn areas with mild detergent. Rinse and dry thoroughly before painting. Unpainted (or unfinished) surfaces should first be primed to ensure an even base color and consistency, before applying the paint.
<b>Application and Clean Up</b>	Under most conditions thinning is not necessary. Stir gently before and during use. Intermix if using multiple containers to ensure color uniformity. Best results are achieved with three coats. Typically dries to the touch in two hours and can be recoated in twenty four. Hardening continues for up to thirty days. Avoid wetting, or scuffing during this period. Can be applied using a good quality synthetic brush; or rolled using a shed resistant 3/8"-1/2" roller cover. Avoid applying below 50°F (10°C).