

SIGNATURE LINE®

IRONWOOD®

95% MOISTURE VAPOR BARRIER,
ELASTOMERIC ADHESIVE

PRODUCT HIGHLIGHT

EXTREMELY
▶ LOW
ODOR



COVERAGE: 20-70 ft²/gal
AVAILABLE IN: 4 gal
SHELF LIFE: 1 year

In the realm of multi-functioning wood adhesives, **Ironwood** nails it. Through its stable, cross-linking chemistry, Ironwood ensures that your flooring stays where you want it. Capable of managing moisture from most concrete slabs, Ironwood is also resistant to high alkalinity.



WHY USE

- 95% moisture protection (porous slab)
- Permanent, waterproof bond
- Solvent and isocyanate-free
- Non-staining and easy to clean
- 1-step installation (no stirring/mixing)
- High-strength, elastomeric membrane
- Rapid occupancy times
- Sound control (IIC, STC)
- Warranted over cutback residue (see TDS)
- Protects flooring from alkali attack
- Extremely low VOC, extremely low odor
- Antimicrobial technology



RH
95%



PH
NTR*
5-14



MVER
15 LBS



OPEN
TIME
0 MIN



WORKING
TIME
45 MIN



CURE
TIME
12 HRS



LIGHT
TRAFFIC
6 HRS



HEAVY
TRAFFIC
6 HRS



ΔIIC
66 dB**



STC
61 dB**