



RH
95%



PH
NTR 5-14



MVER
15 LBS



OPEN TIME
0 MIN



WORKING TIME
45 MIN



CURE TIME
12 HRS



LIGHT TRAFFIC
6 HRS



HEAVY TRAFFIC
6 HRS



STC
61 DB



IIC
66 DB

WHY USE

- 1-part product
- 1-step application
- Antimicrobial technology
- High-strength, elastomeric membrane
- Permanent, waterproof bond
- Easy application
- Easy-to-trowel
- Inhibits mold/mildew growth
- Installs multiple flooring types
- Solvent and isocyanate-free
- LEED v4 contributing: CDPH v1.2
- Modified urethane (isocyanate-free)
- 95% RH moisture protection (porous slab - ASTM F3191)
- 95% moisture vapor barrier
- No shot-/bead-blasting required (CSP 1+)
- No stirring/mixing required
- Non-slump formula
- Non-staining, easy-to-clean
- Extremely low odor
- pH blocker, protects flooring from alkali attack
- Competitive price point
- Rapid access for heavy traffic (6 hrs)
- Rapid access for light traffic (6 hrs)
- Rapid occupancy times (6 hrs)
- Smooths up to 1/8" irregularities
- Sound reduction (3rd party tested)
- Sound reduction and 1/8"-crack isolation
- Extremely low VOCs
- Warranted over cutback residue (see TDS)

CERTIFICATIONS



TRANSPARENCY



LBC VERSION 3.1

APPROVED FLOORING TYPES

FLOORING TYPE	INSTALLATION
RESILIENT	
RUBBER (CRUMB)	
WOOD	
ACRYLIC IMPREGNATED PLANK	
BAMBOO	
CORK FLOORING	
CORK UNDERLAYMENT	
CORK-BACKED HARD SURFACE	
HARDWOOD (ENGINEERED)	
HARDWOOD (PARQUET)	
HARDWOOD (SOLID)	

MEMBERSHIP

